



BOND EXTRA WHITE 607

PRODUCT DESCRIPTION

It is a high polymer modified cement based quick set tile adhesive specially designed for heavy duty applications for Fixing ceramic, vitrified tiles, slabs, natural stones and large size tiles on the interior and exterior wall and floor surfaces. It is highly suggested for exterior areas because it resists thermal expansion. C2TES1 Standard-Regular tile adhesive with zero slip and extended open time.

RECOMMENDED USE

This adhesive is suitable mainly for tiles and stone tiles on exterior wall substrates like plaster or concrete. It is suitable for tiles like ceramic, clay tiles, basalt tiles vitrified, glass mosaic tiles and porcelain tiles and all-natural stone tile.

USES

- Suitable for various tiles, marble granite & other stones.
- Interior application polymer base
- Economical and easy to use
- Bonds to various substrates

FEATURES & BENEFITS

- Very good adhesion
- Non -toxic
- Water cleanup of uncured adhesive
- Very easy to apply

- Dual purpose for wall and floor
- Ideal for new floor & wall tiling.
- Economical

SURFACE PREPARATION

Surface to be cleaned and roughed before installation of tiles and stones.

MIXING INSTRUCTION & APPLICATION

Add 5-to-6-liter clean water with 20kg of SANTEC BOND EXTRA 607 and stir well until a lump free compound is achieved. The surface to be tiled should be clean and sound. Old surfaces must be free from any kind of grease, oils, wax etc. At site addition of water shall be adjusted to attain desired consistency and mix thoroughly until a homogeneous paste is obtained. Allow tiling to set for 24 hours prior to filling joints.

Apply SANTEC BOND EXTRA 607 evenly on the substrate. Use a notched trowel to have a uniform thickness 3mm minimum. Apply the tiles on the substrate and press them firmly, while making sure that the paste does not slip from the tile sides. SANTEC BOND EXTRA 607 can also be applied on the back side of tiles to ensure full adhesion with the entire surface. In case exceptional performance is required.

TECHNICAL DATA

Available Pack Size : 20 Kg

Appearance	White
Tensile Adhesion Standard	C2TES1 (Type 3)

Coverage	20 kg/ 50-60 sqft in 3mm bed thickness
Shelf life	24 months of the original packing in dry environment

CONSUMPTION

3MM Thickness	55-60 sq. ft / 20 kg
----------------------	----------------------

The data given are for guidelines only. The physical values are subject to normal manufacturing tolerances, colour and testing variances. The coverage & consumption figures are theoretical and do not allow for any additional material required due to surface porosity, surface profile, variations in level or wastage etc.

STORAGE & SHELF LIFE

24 months after manufacturing date in original and non-open packaging, under cover, in dry condition, away from humidity, protected from extreme temperatures and direct sunlight.

ANNOTATION

- The surface must be structurally sound, stable, and rigid enough to support ceramic/stone tile, thin brick, and similar finishes.
- Substances deflection under all live, dead, and impact loads, including concentrated loads.
- During cold weather, protect finished work from traffic until fully cured.

- Always use a good quality brush, sponge, scrubber or white cotton cloth while applying to avoid damaging the surface due to the decolorization.
- While using any tools like spray pumps, low hand pressure pumps, water jets, mixer machines, grinding machines in application, clean the inner and outer surface of the tool to avoid any kind of damage to the surface and material to be used.

HEALTH & SAFETY

Precautions

- During application wear protective clothing, gloves and eye goggles during application. Avoid products to contact eyes and skin.
- Keep out of reach of children.
- Not for internal consumption.
- Apply between temp. 5°C to 35°C.
- Use only in well ventilated areas.
- Wash hands thoroughly after applying.

Accident

- Use water spray.

Spillage

- Take up mechanically or with absorbent material.

First Aid

- If swallowed, contact a physician.
- If in skin contact wash skin with water and remove contaminated clothing.
- If you come in contact with the eye, hold open, flood with water for at least 10 min and contact a physician.

NOTES

The information above is believed to be accurate and represents the best information currently available to Santec Chemical Private Limited. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall the Santec Chemical Private Limited be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, however arising, even if the company has been advised of the possibility of such damages.

COMPANY DETAILS

Corporate Office : SANTEC CHEMICAL
PRIVATE LIMITED, Malappuram, Kerala, India.

Call : +91 7247 555 666

E-mail : info@santecchemicals.com

Website : www.santecchemicals.com

For feedback or complaints, write to Marketing Manager Services on the above mentioned address.